U Série 3.5 T



NEV

U Series TRAILER

Facilitates the handling of motor boats up to 3.6 T and 9 M

With an innovative concept, the U Series trailer combines all the advantages of a road trailer and a small hydraulic cradle at an attractive cost. This hybrid trailer is specially designed for on-site handling of motorboats up to 3.6 T and 9 M (workshop storage) and for launching and hauling operations at the beginning and end of the season.



The trailer, open at the rear, moves back under the boat placed on 2 special cradles with 3 support points. The driver positions the cradles in the middle of the trailer.

The boat cornes into contact with 7 balancers mounted on 14 hydraulic cylinders which will lift it up to 300 mm.

The boat can then be winched up to the bow stop.





The hitch is ready to set off after securing the boat and closing the crossbar back.



Launch rotations ultra-fast

Optimised for handling time and security

2 models for transport 90% of the boat fleet

Launching

The trailer is semi-submerged. The adjustment of the hydraulic jacks makes it possible to create a slope suitable for launching into the water.

Water outlet

The trailer is semi-submerged. Its central opening allows the boat to move forward freely' until it cornes into contact with the outriggers. Guides allow the boat to be centered. The hydraulic system lifts the boat (stroke up to 300 mm). Secured to the winch, it is no longer in contact with the water. The trailer can move forward. Rinsing the traiter at the end of the day is essential.

Road approval

Up to 3.5 T PTAC. Beyond that, use same as CHS.

Stainless steel hydraulic kit optional

2-year maintenance contract on the brake system included (parts and labor) or required annual maintenance.

GENERAL CHARACTERISTICS										REF. TRAILERS		REF. CRADLES	
MODEL	Length boat	PTAC	No. of points lifting	No. of jacks by point	Axles braked	Gallows adjustable	Hydroelectric controls	Kit hydraulic stainless steel	Kit Quickflex	Standard	Version stainless steel	Cradles 2 T AV	Cradles 2 T AR
U Serie - 7 m	5 to 8 m	3,5 T	5 double	10	•	•	option	option	option	MP-U3.5T	MP-U3.5T INOX	MP-BS040AVT	MP-BS040ARR
U Serie - 8 m	5,5 to 9 m	5 T	7 double	14	•	•	•	option	option	MP-U5T	MP-U5T INOX		



U Series TRAILER









